



Rotary lock

made of stainless steel

ROTARY LOCK WITH RECTANGULAR OPENING, FOUR-SIDED SEALING

Size and barrier pressure on the front

- 200 x 200 mm to 4000 x 1500 mm
- Barrier pressure: 6 mWC; higher pressure levels possible

Flap

- Flap cover reinforced by means of internal sheet metal ribs according to static requirements

Material

- 1.4301 (304) / 1.4404 (316L) / 1.4410 (507) / 1.4462 (318LN) / 1.4539 (904L) / 1.4571 (316Ti)

Tightness class

- Leakage rate to DIN EN 19569, Part 4, Table 1:
Pressure at front: 0.05 to $0.1 \text{ l} \cdot \text{s}^{-1} \cdot \text{m}^{-1}$ (tightness class 3)

Mounting

- Dowel to the wall in front of the opening

Scope of delivery

- Rotary lock complete with all required fastening elements (dowels and sealing material)



Rotary lock 2600 × 1100 mm



Two rotary locks, each 2600 × 1100 mm

i

YOUR ADVANTAGES

- **VERSATILE**
Soft-sealing rotary lock as a backflow preventer, for drainage and flood protection
- **LASTES FOREVER**
Replaceable wear parts and seal (EPDM or NBR)
- **FACTORY CERTIFICATE**
Rotary lock including factory certificate according to DIN EN 10204, 2.1, with indication of the leakage rate according to DIN 19569, part 4
- **PERFECT CORROSION PROTECTION**
All welded stainless steel parts from our own pickling plant

2021-04-19-en