



## MOBITORQ accu

Battery operated mobil actuator

### Technical data

- Torque: 5-500 Nm
- Torque settings: 60-stage (4 gears each with 15 setting stages)
- Speed: 0-152 rpm
- Charger mains voltage: 220-240V/50-60Hz
- Battery pack voltage: 18 V
- Battery pack capacity: 6.0 Ah
- Battery pack weight: 0.6 kg
- Power tool weight: 5.1 kg
- Tool socket: Standard square 1-inch

### StarterSet

Battery operated mobil actuator up to 500 Nm torque

- 2 battery packs 18 V/6.0 Ah
- Battery charger 230 V
- Handrail
- Telescopic drive rod 500-800 mm
- Coupling sleeve 27/30 mm
- Pusher
- Hexagonal wrench

### BasicSet

Battery operated mobil actuator up to 500 Nm torque

**Consisting of StarterSet and additional:**

- Transport case with wheels

### ProfiSet

Battery operated mobil actuator up to 500 Nm torque

**Consisting of BasicSet and additional:**

- Coupling sleeve 12/14 mm
- Universal handwheel claw with 5 driving elements
- Drive rod, short 500 Nm
- Short adapter 230 Nm



MOBITORQ accu



MOBITORQ accu battery pack 6.0 Ah



MOBITORQ accu charger



MOBITORQ accu wheeled case with ProfiSet



Universal handwheel claw from above (left) and below (right)



Drive rod 500 Nm



Short adapter 230 Nm



Conical coupling sleeve 12



1. Handrail  
2. Drive rod

## YOUR ADVANTAGES

- Very large range of use due to fine-meshed preselection stages of gear and cut-off torques within the range of approx. 5-500 Nm.
- Also ideal for house connection extensions as, within the lowest gear stage, it is possible to operate with minimum torques of 5 Nm.
- Especially where large valves with long traversing distances are concerned, the fast running gear saves working time.
- The working speed remains finely adjustable in each gear, to move into the end positions without damaging the material.
- Powerful 6.0 Ah power packs ensure long staying power, even at high torques.
- The tool socket corresponds to the standard square 1-inch.
- Extensive accessories matched to the work situation.

